

3 Horse Angle Load Trailer Standard

1. Basic configuration (AX-3HAL-S)

Trailer Materials	Chassis Material	double hot dip galvanized RHS (3.5mm-5.0mm)
	Frame Material	double hot dip galvanized RHS (2.5mm)
	Body Panel	galvanized sheet (1.0-1.5mm)
	Roof	Special molded FRP 4575x1980,3mm
	Nuts&Bolts	Stainless steel
Wheels & Tyres	Wheel Rim	14' aluminum alloy rims
	Tyres	Five 185R14C GITI tyres (includes a spare tyre)
Axles & Suspensions	Axles	Two special trailer axles 50x50mm
	Leaf Springs	Roll rocker tandem spring 7 plates
	Brake System	Double axle with electric brakes, front axle also with hand brake
Windows & Doors	Front Window	1220x610 mm
	Side Windows	2 drop down windows: 790x519mm & 3 sliding windows: one 600*300mm and two 900x300mm
	Vents	Two large size double-open skylights
	Side Door	1675x670mm
	Rear Upper Door	1980x1065mm
	Ramp Door	2030x1210mm
	Rear Upper&Ramp Door Strut	High-intensity anti-rust strut
	Hinges For Rear Upper Door	Special 6mm diameter copper hinges
Draw Bar	Couplings	50mm ball coupling
	Drawbar Checker Plate	1.2mm aluminum checker plate
	Drawbar Safety Chain	Two
	Bracing Wheel	One
Lights & Retro Reflectors	Trailer Plugs	Seven-prongs Plug
	Inner Lights	Two touch switch LED lights
	Rear Lights	Two LED combination taillights
	Width Lights	Six width LED lights
	License Plate	One
Retro Reflectors	8	
Mudguard	Mudguard Type	External mudguards
	Mudguard Checker Plate	1.2mm aluminum checker plate in the front of mudguards
	Pedal& Aluminium Step	1.2mm aluminum checker plate
Floor & Rubber Matting	Rubber mattering for floor	whole sheet 8mm rubber matting
	Rubber Matting for Ramp Door	10mm
	Rubber Matting for Inner Side Panel	6mm
	Aluminum for floor	3mm aluminum